



TYPICAL EXT. STUCCO WALL CONSTRUCTION
 PLASTER (DOUBLE COAT)
 GALV. EXPANDED METAL LATH
 WATERPROOF BUILDING PAPER
 7/16" OSB PANEL SHEATHING
 TYPE 1 EXPANDED POLY-STYRENE (1 LB DENSITY) INSULATION PANEL
 2x4 STUD WALL @ 16" O.C.
 1/2" AIR SPACE
 6mil POLY AIR VAPOUR BARRIER
 1/2" GYPSUM BOARD

7 3/8" TOTAL ASSEMBLED WALL THICKNESS

REMOVABLE BREAKAWAY CHANNELS (VERTICAL) 2" ON BOTH SIDES OF EACH STUD x 1 1/2" DEEP (2 1/2" BEHIND DRYWALL FACE).

2 REMOVABLE BREAKAWAY CHANNELS (HORIZONTAL) 3" HIGH x FULL WIDTH x 1 1/2" DEEP 48" & 51" OFF FLOOR FOR SWITCHES

2 REMOVABLE BREAKAWAY CHANNELS (HORIZONTAL) 3" HIGH x FULL WIDTH x 1 1/2" DEEP 14" & 17" OFF FLOOR FOR RECEPTACLES

ICF FOUNDATION WALL (6" THICK WITH SHOWN)

	STUCCO WALL SECTION (ICF FOUNDATION & PARAPET ROOF)	
	EZ SIPS	
DATE:	MAR-02-14	
SCALE:	3/4"=1'-0"	
REVISION:	-	
DWG NO:	EZ SIPS-2x4 / 5D	
NK CAD DESIGN www.NKCADD.COM 519-865-8460		