



2x6 TOP PLATE

REMOVABLE BREAKAWAY CHANNELS  
(VERTICAL) 2" ON BOTH SIDES OF EACH  
STUD x 1 1/2" DEEP (2 1/2" BEHIND DRYWALL FACE).

**TYPICAL EXT. STUCCO  
WALL CONSTRUCTION**  
PLASTER (DOUBLE COAT)  
GALV. EXPANDED METAL LATH  
WATERPROOF BUILDING PAPER  
7/16" OSB PANEL SHEATHING  
TYPE 1 EXPANDED POLY-STYRENE  
(1 LB DENSITY) INSULATION PANEL  
2x6 STUD WALL @ 16" O.C.  
1/2" AIR SPACE  
6mil POLY AIR VAPOUR BARRIER  
1/2" GYPSUM BOARD

2 REMOVABLE BREAKAWAY CHANNELS  
(HORIZONTAL) 3" HIGH x FULL WIDTH x 1 1/2" DEEP  
48" & 51" OFF FLOOR FOR SWITCHES

9" TOTAL ASSEMBLED  
WALL THICKNESS

2 REMOVABLE BREAKAWAY CHANNELS  
(HORIZONTAL) 3" HIGH x FULL WIDTH x 1 1/2" DEEP  
14" & 17" OFF FLOOR FOR RECEPTACLES

2x6 BOTTOM PLATE

1 3/4" EZ SHEET

WEEP SCREED

POURED/BLOCK FOUNDATION WALL  
(8" THICK SHOWN)



TYPICAL STUCCO WALL SECTION  
WITH INSULATED RIM JOIST  
(POURED/BLOCK FOUNDATION)

**EZ SIPS**

DATE: FEB-02-14	DRAWN: OC
SCALE: 3/4"=1'-0"	APPROVED:
DWG NO: EZ SIPS-2X6 / 5B	