

TYPICAL EXT. STUCCO
 WALL CONSTRUCTION
 PLASTER (DOUBLE COAT)
 GALV. EXPANDED METAL LATH
 WATERPROOF BUILDING PAPER
 7/16" OSB PANEL SHEATHING
 TYPE 1 EXPANDED POLY-STYRENE
 (1 LB DENSITY) INSULATION PANEL
 2x6 STUD WALL @ 16" O.C.
 1/2" AIR SPACE
 6mil POLY AIR VAPOUR BARRIER
 1/2" GYPSUM BOARD

9" TOTAL ASSEMBLED
WALL THICKNESS

2x6 BOTTOM PLATE

WEEP SCREED


ICF FOUNDATION WALL
(6" THICK WITH SHOWN)

2x6 TOP PLATE

REMOVABLE BREAKAWAY CHANNELS
(VERTICAL) 2" ON BOTH SIDES OF EACH
STUD x 1 1/2" DEEP (2 1/2" BEHIND DRYWALL FACE).

2 REMOVABLE BREAKAWAY CHANNELS
(HORIZONTAL) 3" HIGH x FULL WIDTH x 1 1/2" DEEP
48" & 51" OFF FLOOR FOR SWITCHES

2 REMOVABLE BREAKAWAY CHANNELS
(HORIZONTAL) 3" HIGH x FULL WIDTH x 1 1/2" DEEP
14" & 17" OFF FLOOR FOR RECEPTACLES

	STUCCO WALL SECTION (ICF FOUNDATION)	
	EZ SIPS	
	DATE: FEB-02-14	DRAWN: OC
	SCALE: 3/4"=1'-0"	APPROVED:
DWG NO: EZ SIPS-2X6 / 5C		